

From: MULTICYL Inc. <sales@multicyl.com>

Subject: Press-In-A-Box - Set-Up in Minutes - News from MULTICYL Inc.

Reply: sales@multicyl.com

Having trouble viewing this email? [Click here](#)

You're receiving this email because of your relationship with MULTICYL Inc. Please [confirm](#) your continued interest in receiving email from us. To ensure that you continue to receive emails from us, add sales@multicyl.com to your address book today.

You may [unsubscribe](#) if you no longer wish to receive our emails.

Quick Links

[Multicyl.com](#)

[Newsletters](#)

[Videos](#)

[Press Selection Tool](#)

[Punching Basics Guide](#)



February 2012

Ever needed to have a flexible press that can be setup in minutes? Multicyl offers the "**Press-In-A-Box™**". It really can't be any simpler; it goes from box to a press "**in 5 minutes or less**". All you need is a supply of shop air. _____

The Multicyl Press-In-A-Box™ consists of 4 different components:

1. The **Multicyl cylinder**. The cylinders are available in a different tonnage combinations ranging from 2-1/2 to 40 tons.
2. The **Multicyl cage**, there are standard cages for both tube punching tools and regular unitized tooling.
3. **Tooling**. Unitized tooling is available for a variety of applications. Round holes, shaped holes, slots, and notches are all examples of available tooling. Sheet metal, angle, and tubing can all be punched by Press-In-A-Box systems.
4. **Air controls**. Air controls are available in a variety of formats, including standard foot valve, two hand anti tie down, or a solenoid packages.

Once all the components are unboxed, the cage with the tooling pre-installed prior to shipping is mounted on a bench, the Multicyl is threaded into place, and then the air controls are installed according to the schematic, and tied into existing shop air. It is that simple - you can literally **be punching parts in under 5 minutes** with the power of

Multicyl.



**FREE
Tonnage
Calculator**

Use our [Tonnage Calculator](#) to determine your force requirements.

To use our tonnage calculator select either the hole diameter or shear length option. Then select your material or fill in the tensile strength of the material you are using (KSI). Fill in the rest of the data and hit calculate. You will be given the tonnage requirement and a list of potential Multicyl cylinders for the application.

Contact us for a free quote on your application

www.multicyl.com punch@multicyl.com

Tel. 905.951.0670 US Toll Free. 800.388.6359 Fax. 905.951.0672

[Forward email](#)



This email was sent to sales@multicyl.com by sales@multicyl.com | [Update Profile/Email Address](#) | Instant removal with [SafeUnsubscribe™](#) | [Privacy Policy](#).

MULTICYL Inc. | 640 Hardwick Road, Unit 1 | Bolton | Ontario | L7E 5R1 | Canada